

RT-MAXH Hollow drill bits Dustlessdrill SDS max

Hollow drill bits SDS max for dust-free drilling in reinforced concrete



Certificate



Product information

Features and benefits

- Two holes in the tip of the drill bit allows you to drill and extract dust simultaneously (due to the possibility of fastening a vacuum cleaner)
- Drilling, along with dust extraction, make the hole smooth and clean
- Quick removal of dust increases drilling speed and enhances drill bit durability (reduces friction)
- Drilled holes do not require cleaning before fastening, which greatly reduces assembly time
- Rubber adapter, which is built-in the bit, enables you to fasten a vacuum cleaner hose and to drill holes without dust
- 3 deep-seated carbide plates significantly increase the service life and efficiency of the drill bit
- 6 cutting edges increase the efficiency of drilling and speeds up hole drilling
- Centring point for quick commencement of drilling without the drill slipping
- Optimized drill bit geometry allows making axial and cylindrical holes, perfect for mounting
- Steel with specification 34CrNiMo6 provides high strength and durability
- Extremely high quality, cylindricity and axial alignment of drilled holes, confirmed by international Sicher Safe certificate

Applications

- Drilling holes in reinforced concrete, concrete, stone and hard brick

Base materials

- Reinforced concrete
- Concrete
- Solid Brick
- Solid Concrete Block

Corresponding products

- R-KEX II with Post-Installed Rebars
- R-KEX II with Rebars as an Anchor
- R-KER with Post-Installed Rebars
- R-KER with Rebar as an Anchor

Attention



Technical Data

Index	Drill diameter	Length	Working length	Quantity	Box weight	Outer weight	EAN
	[mm]	[mm]	[mm]	[pcs]	kg	kg	
RT-MAXH-14/600	14	600	400	1	0.82	4.11	5906675397085
RT-MAXH-16/600	16	600	400	1	0.92	4.59	5906675397092
RT-MAXH-18/600	18	600	400	1	0.99	4.97	5906675397108
RT-MAXH-20/600	20	600	400	1	1.13	5.64	5906675397115
RT-MAXH-22/600	22	600	400	1	1.13	5.64	5906675397122
RT-MAXH-25/600	25	600	400	1	1.12	5.62	5906675397139
RT-MAXH-28/600	28	600	400	1	1.29	6.44	5906675397146
RT-MAXH-30/600	30	600	400	1	1.44	7.18	5906675397153
RT-MAXH-32/600	32	600	400	1	1.48	7.40	5906675397160
RT-MAXH-35/600	35	600	400	1	1.59	7.93	5906675397177